

# Product data sheet

Specifications



APC Smart-UPS X, Line Interactive,  
1500VA, Rack/tower convertible  
2U, 120V, 8x 5-15R NEMA,  
SmartConnect port, Extended  
runtime, TAA

SMX1500RM2UCUS

## Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Input Connection Type	NEMA 5-15P
Nb of power socket outlets	8 NEMA 5-15R
Provided equipment	CD with software

## Physical

Color	Black
-------	-------

## Input

Efficiency at full load	75...154 V adjustable
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

## Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

## Environmental

Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Batteries & Runtime

Battery power in VAh	288 VAh runtime
Battery Charge Power (Watts)	103 W rated
Battery option	SMX48RMBP2U 5 939 VAh

## Ordering and shipping details

GTIN	731304424468
------	--------------

# Offer Sustainability

---

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

---